



BY TAYLOR®

SOFT SERVE YOU CAN COUNT ON. SUPPORT YOU ALREADY TRUST.

THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS. ICETRO BY TAYLOR OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.





ENGINEERED FOR RELIABILITY, BACKED BY TAYLOR'S TRUSTED SERVICE AND SUPPORT. CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE. WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/



Model No.	ISI-161TH	ISI-161TI	ISI-163TT	ISI-203SN	ISI-203SNN	ISI-271SHSN	ISI-271THSN	ISI-300TA	ISI-301TH	ISI-303SNA
Flavors	1	1	2 + Twist	2 + Twist	2 + Twist	1	1	1	1	2 + Twist
Mix Pump	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed	Gravity Fed
Installation	Countertop	Countertop	Countertop	Freestanding	Freestanding	Freestanding	Countertop	Countertop	Countertop	Freestanding
Heat Treatment	Yes	No	No	No	No	Yes	Yes	No	No	No
Hopper	3.2 QT	3.2 QT	(2) 5.9 QT	(2) 10.1 QT	(2) 10.1 QT	13.3 QT	13.3 QT	18.5 QT	18.5 QT	(2) 19 QT
Cylinder	1.5 QT	1.5 QT	(2) 1.7 QT	(2) 2.9 QT	(2) 2.9 QT	2.9 QT	2.9 QT	3.4 QT	3.4 QT	(2) 3.6 QT
Capacity	Low	Low	Medium	Medium	Medium	High	High	High	High	High
Dispensing Capacity (3oz servings)	3	3	7-8	12-14	12-14	Indefinite 2.7oz	Indefinite 2.7oz	11-12	11-12	23-25
Electrical Options	115V/60Hz 1p	115V/60Hz 1p	230V/60Hz 1p	230V/60Hz 1p	230V/60Hz 3p	230V/60Hz 1p	230V/60Hz 1p	230V/60Hz 1p	230V/60Hz 1p	230V/60Hz 3p
Circuit Breaker Amp Minimum	20	20	23	30	18	15	19	13	19	31
Compressor (HP)	0.85	0.85	0.85	1	1	1.5	1.5	1.5	1.5	2
Drive Motor (HP)	0.5	0.5	0.5	1	1	1	1	1	1	1
Dimensions (WxDxH)	11.8"x30.5"x33"	11.8"x30.5"x33"	20"x29.3"x31.6"	20.9"x33.3"x59.1"	20.91"x33.3"x59.1"	14.96"x33.15"x54.7"	14.96"x37.6"x38.9"	18.1"x33.1"x36.2"	18.1"x33.1"x36.2"	26.3"x36.4"x59.8"
Taylor Model Comparison	C152	C152	C161	C723 with cart C791	C723 with cart C791	N/A	N/A	C707	C709	C713, C794