

**SOFT SERVE YOU
CAN COUNT ON.
SUPPORT YOU ALREADY TRUST.**



BY TAYLOR®



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE
WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/**



Model Number ISI-161TH I16112D717 SOFT SERVE FREEZER

FEATURES

Flavor You Can Count On:

Compact Single Flavor, Gravity Fed, Hopper Agitator, Heat Treatment.

Compact Menu Versatility:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, in a compact configuration designed for dependable daily operation.

Automated Heat Treatment System:

Daily heating and cooling cycles safely maintain dairy products for up to 28 days before full disassembly and cleaning is required, supporting longer run times and reduced maintenance frequency.

Consistent Production Performance:

One 1.5-quart (1.4 liter) freezing cylinder delivers smooth texture and reliable output throughout the day.

Refrigerated Mix Protection:

One 3.2-quart (3 liter) hopper with separate hopper refrigeration (SHR) maintains mix below 41°F (5°C) in Auto and Standby modes, preserving product quality and food safety.

Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

SPECIFICATIONS

Weights	lbs.	kgs.
Net	196	89
Crated	238	108
<i>*For reference only.</i>		
	cu. ft.	cu. m.
Volume	18.53	0.52
Dimensions	in.	mm.
Width	11.8	300
Depth	30.5	775.9
Height	33	838

**Designed to rest on a plastic pad directly on counter top.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Supplied NEMA Cord
115/60/1			13.2	NEMA 5-20P



To Contact a Distributor visit.
www.taylor-company.com/distributors

750 N. Blackhawk Blvd.
Rockton, Illinois 61072