

**SOFT SERVE YOU  
CAN COUNT ON.  
SUPPORT YOU ALREADY TRUST.**



**BY TAYLOR®**



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.  
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND  
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE  
[WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/](http://WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/)**



# Model Number ISI-163TT I16327D327 SOFT SERVE FREEZER

## FEATURES

### Flexible Flavor Offerings:

Compact Twin Twist, Gravity Fed, Hopper Agitator.

### Expanded Flavor Options:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, across multiple dispensing options in a compact footprint.

### Consistent Production Performance:

Two 1.7-quart (1.6 liter) freezing cylinders deliver steady production and smooth texture for both dispensing sides.

### Refrigerated Mix Protection:

Two 5.9-quart (5 liter) hoppers with separate hopper refrigeration (SHR) maintain mix below 41°F (5°C) in Auto and Standby modes to preserve freshness and food safety.

### Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

### Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

### Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

### Security When You Need It:

Two-locking front locking casters keep the unit firmly in place during operation. When it's time to clean, simply unlock and move it with ease. Stability and flexibility, built in.

## SPECIFICATIONS

| Weights | lbs. | kgs. |
|---------|------|------|
| Net     | 395  | 179  |
| Crated  | 430  | 195  |

*\*For reference only.*

|            | cu. ft. | cu. m. |
|------------|---------|--------|
| Volume     | 29.14   | 0.82   |
| Dimensions | in.     | mm.    |
| Width      | 20      | 510    |
| Depth      | 29.3    | 745    |
| Height     | 31.6    | 803    |

*\*Designed to rest on a plastic pad directly on counter top or optional cart.*

| Electrical       | Maximum Fuse Size | Minimum Circuit Ampacity | Total Ampacity | Poles (P) Wires (W) |
|------------------|-------------------|--------------------------|----------------|---------------------|
| 208-230/60/1 Air | 28                | 23                       | 22             | 2P 3W               |



To Contact a Distributor visit.  
[www.taylor-company.com/distributors](http://www.taylor-company.com/distributors)

750 N. Blackhawk Blvd.  
Rockton, Illinois 61072