

**SOFT SERVE YOU
CAN COUNT ON.
SUPPORT YOU ALREADY TRUST.**



BY TAYLOR®



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE
WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/**



Model Number ISI-203SNN I20333D328 SOFT SERVE FREEZER

FEATURES

Flexible Flavor Offerings:

Twin Twist, Gravity Fed.

Consistent Flavor Performance:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, in a model designed to maintain smooth output during extended service periods.

Consistent Production Performance:

Two 2.9-quart (2.7 liter) freezing cylinders deliver steady production and smooth texture during peak demand.

Refrigerated Mix Protection:

Two 10.1-quart (9.6 liter) hoppers with separate hopper refrigeration (SHR) maintain mix below 41°F (5°C) in Auto and Standby modes to preserve freshness.

Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

Security When You Need It:

Two-locking front locking casters keep the unit firmly in place during operation. When it's time to clean, simply unlock and move it with ease. Stability and flexibility, built in.

SPECIFICATIONS

Weights	lbs.	kgs.
Net	586	266
Crated	654	297

**For reference only.*

	cu. ft.	cu. m.
Volume	64.18	1.81

Dimensions	in.	mm.
Width	20.9	531
Depth	33.3	846
Height	59.1	1501

**Mounted on standard casters.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Poles (P) Wires (W)
208-230/60/3 Air	20	18	18	3P 4W



To Contact a Distributor visit:
www.taylor-company.com/distributors

750 N. Blackhawk Blvd.
Rockton, Illinois 61072