

**SOFT SERVE YOU
CAN COUNT ON.
SUPPORT YOU ALREADY TRUST.**



BY TAYLOR®



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE
WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/**



Model Number ISI-271SHSN I27127D718 SOFT SERVE FREEZER

FEATURES

Flavor You Can Count On:

Semi Automatic Vending Slim Single Flavor, Gravity Fed, Hopper Agitator.

Streamlined Soft Serve Variety:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, in a configuration developed for reliable operation across diverse locations.

Consistent Production Performance:

One 2.9-quart (2.7 liter) freezing cylinder delivers smooth texture and steady output.

Refrigerated Mix Protection:

One 13.3-quart (12.3 liter) hopper with separate hopper refrigeration (SHR) maintains mix below 41°F (5°C) in Auto and Standby modes to preserve product integrity.

Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

Security When You Need It:

Two-locking front locking casters keep the unit firmly in place during operation. When it's time to clean, simply unlock and move it with ease. Stability and flexibility, built in.

SPECIFICATIONS

Weights	lbs.	kgs.
Net	313	141
Crated	369	167

**For reference only.*

	cu. ft.	cu. m.
Volume	42.38	1.20
Dimensions	in.	mm.
Width	14.96	380
Depth	33.15	842
Height	54.7	1390

**Mounted on standard casters.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	20	15	14	2P 3W



To Contact a Distributor visit.
www.taylor-company.com/distributors

750 N. Blackhawk Blvd.
Rockton, Illinois 61072