

**SOFT SERVE YOU
CAN COUNT ON.
SUPPORT YOU ALREADY TRUST.**



BY TAYLOR®



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE
WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/**



Model Number ISI-271THSN I27127D717 SOFT SERVE FREEZER

FEATURES

Flavor You Can Count On:

Semi Automatic Vending Slim Single Flavor, Gravity Fed, Hopper Agitator.

Soft Serve Flexibility for Limited Spaces:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, in a profile designed to fit where traditional equipment cannot.

Consistent Production Performance:

One 2.9-quart (2.7 liter) freezing cylinder supports steady production and smooth texture.

Refrigerated Mix Protection:

One 13.3-quart (12.3 liter) hopper with separate hopper refrigeration (SHR) maintains mix below 41°F (5°C) in Auto and Standby modes to protect quality.

Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

SPECIFICATIONS

Weights	lbs.	kgs.
Net	313	142
Crated	369	167

**For reference only.*

	cu. ft.	cu. m.
Volume	34.2	0.97

Dimensions	in.	mm.
Width	14.96	380
Depth	37.6	955
Height	38.9	989

**Designed to rest on a plastic pad directly on counter top.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	25	19	16	2P 3W



To Contact a Distributor visit:
www.taylor-company.com/distributors

750 N. Blackhawk Blvd.
Rockton, Illinois 61072