

**SOFT SERVE YOU
CAN COUNT ON.
SUPPORT YOU ALREADY TRUST.**



BY TAYLOR®



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE
WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/**



MODEL ISI-300TA SOFT SERVE FREEZER

FEATURES

Flavor You Can Count On:

Single Flavor, Gravity Fed, Hopper Agitator.

High-Output Menu Versatility:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, in a configuration suited for sustained daily production.

Consistent Production Performance:

One 3.4-quart (3.2 liter) freezing cylinder delivers dependable output and smooth consistency.

Refrigerated Mix Protection:

One 18.5-quart (17.5 liter) hopper with separate hopper refrigeration (SHR) maintains mix below 41°F (5°C) in Auto and Standby modes, reducing refill frequency while preserving quality.

Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

SPECIFICATIONS

Weights	lbs.	kgs.
Net	309	140
Crated	334	151

**For reference only.*

	cu. ft.	cu. m.
Volume	33.84	0.96
Dimensions	in.	mm.
Width	18.1	460
Depth	33.1	841
Height	36.2	919

**Designed to rest on a plastic pad directly on counter top.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	18	13	12	2P 3W

I30027D327



To Contact a Distributor visit.
www.taylor-company.com/distributors

750 N. Blackhawk Blvd.
Rockton, Illinois 61072