

**SOFT SERVE YOU
CAN COUNT ON.
SUPPORT YOU ALREADY TRUST.**



BY TAYLOR®



**THE NEW NAME IN RELIABLE, EASY-TO-OPERATE SOFT SERVE FREEZERS.
ICETRO OFFERS PRACTICAL MODELS DESIGNED FOR DAY-TO-DAY PERFORMANCE AND
BACKED BY TAYLOR'S GLOBAL SERVICE AND SUPPORT NETWORK.**

**CONTACT YOUR LOCAL TAYLOR DISTRIBUTOR TO LEARN MORE
WWW.TAYLOR-COMPANY.COM/DISTRIBUTORS/**



Model Number ISI-303SNA I30333D328 SOFT SERVE FREEZER

FEATURES

Flavor You Can Count On:

Single Flavor, Gravity Fed, Hopper Agitator.

Steady Soft Serve Production:

Offer all the popular soft serve variations, from low-fat to non-fat options or yogurt, in a configuration designed for consistent performance throughout the day.

Consistent Production Performance:

One 3.6-quart (3.4 liter) freezing cylinder delivers reliable output and consistent soft serve texture.

Refrigerated Mix Protection:

One 19-quart (18 liter) hopper with separate hopper refrigeration (SHR) maintains mix below 41°F (5°C) in Auto and Standby modes to preserve freshness and food safety.

Operational Awareness:

Mix Low and Mix Out indicator lights alert operators when product needs replenishing. An optional audible alarm adds visibility during busy periods, and automatic shutdown protects the unit if mix is depleted.

Precision Monitoring and Control:

Integrated microprocessor touch controls display hopper and freezing cylinder temperatures at any point during operation while maintaining smooth, consistent soft serve texture for up to two hours without dispensing.

Energy-Conscious Standby Mode:

During extended no-use periods, Standby maintains safe product temperatures in both the mix hopper and freezing cylinder, preserving quality while reducing unnecessary operation.

Security When You Need It:

Two-locking front locking casters keep the unit firmly in place during operation. When it's time to clean, simply unlock and move it with ease. Stability and flexibility, built in.

SPECIFICATIONS

Weights	lbs.	kgs.
Net	765	347
Crated	841	381

**For reference only.*

	cu. ft.	cu. m.
Volume	89.33	2.53
Dimensions	in.	mm.
Width	26.3	668
Depth	36.4	925
Height	59.8	1519

**Mounted on standard casters.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Poles (P) Wires (W)
208-230/60/3 Air	35	31	30	3P 4W



To Contact a Distributor visit.
www.taylor-company.com/distributors

750 N. Blackhawk Blvd.
Rockton, Illinois 61072