

LINCAT SILVERLINK ELECTRIC COUNTER-TOP BAIN MARIE - DRY HEAT - GASTRONORMS - BASE + DISH PACK - W 450 MM - 0.75 KW

MODEL: BM4A



Do you need to safely hold sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature? This Silverlink 600 Electric Dry Heat Bain Marie does just that. Perfect for takeaways, restaurants and mobile caterers, the bain marie is designed to plug in and play so you'll be serving delicious dishes in no time. With 2 x 1/2 150mm deep gastronorms and lids included, the unit also comes with an adjustable temperature control.

SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CC4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 450 mm
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand for units W 450 mm
- HC4 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 450 mm - 0.5 kW
- HCL4 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 450 mm - 0.5 kW

PRODUCT FEATURES

- Dry heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 2x 1/2 150mm deep gastronorms with lids are included
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & pre-cooked foods
- Adjustable temperature control







LINCAT SILVERLINK ELECTRIC COUNTER-TOP BAIN MARIE - DRY HEAT - GASTRONORMS - BASE + DISH PACK - W 450 MM - 0.75

MODEL: BM4A

WEIGHTS & DIMENSIONS	
Width	450 mil
Depth	600 mil
Height	290 mil
Weight	13.5 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	55 cm
Ship Height	49.5 cm
Ship Weight	14.85 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

or Wires

PRODUCT CERTIFICATIONS



ENERGY SPECS		
Primary Energy Source Type	Electricity	Number of Electrical Conducto
Electrical Amps	3.3	Electrical Connection Type
Electrical Voltage	230 volts	Electrical Plug Type
Electrical Watts	750	Number of Electrical Plugs
Electrical Phase	Single	Dedicated Circuit Required
Kilowatts	0.75 kW	Energy Saving

ADDITIONAL SPECIFICATIONS			
Control Type	Rotary Control Knob	Modular	Yes
Drain	No	Mounting Position	Top Mount Drop-In
Gastronorm Capacity	2 x GN1/2	Number of Wells	2
Hot Food Well Application Type	Dry	Waterless	Yes
Insulated	No	Well Shape	Rectangle

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

1

1 No No

Cord and Plug UK 3-Pin Plug










MODEL: BM4A

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024