

LINCAT SILVERLINK NATURAL GAS COUNTER-TOP GRIDDLE -STEEL PLATE - W 450 MM - 5.4 KW

MODEL: GS4/N



Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Gas Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and an easy to clean surface, while the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results. The griddle, perfect for cafes, pubs and restaurants, comes with piezo ignition for easy lighting of the burners.

PRODUCT OPTIONS AND ACCESSORIES

- SB4 450 GRIDDLE SPLASHB
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand for units W 450 mm

PRODUCT FEATURES

- 12 mm v machined steel plate providing even heat distribution and an easy to clean surface
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- · Front mounted control for easy of use during cooking
- Piezo ignition for easy lighting of the burners
- Flame failure device for maximum safety







LINCAT SILVERLINK NATURAL GAS COUNTER-TOP GRIDDLE -**STEEL PLATE - W 450 MM - 5.4 KW**

MODEL: GS4/N

WEIGHTS & DIMENSIONS	
Width	450 mil
Depth	650 mil
Height	415 mil
Weight	35.1 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	55 cm
Ship Height	63.5 cm
Ship Weight	38.61 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS	
Primary Energy Source Type	Gas
Kilowatts	5.4 kW
Electrical Connection Type	Not Applicable
Electrical Plug Type	Not Applicable
Number of Electrical Plugs	Not Applicable
Gas Type	Natural Gas

Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	16 mBar
Gas Total BTUs	18425 BTU
Gas Consumption at Max Use Per Hour	0.51 m ³
Total Heat Input at Max Use	5.4 kW, 16700 BTU per hour
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Control Type	Mechanical
Cooking Area Plate Depth	405 mm
Cooking Area Plate Width	412 mm
Cooking Plate Finish Material Type	Polished Steel
Legs or Casters	Not Applicable
Lower Platen Surface Type (multi-select)	Smooth

Number of Burners	2
Number Of Controls	2
Number of Heating Zones	2
Plate Shape	Rectangle
Plate Thickness	12 mm
Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024










MODEL: GS4/N

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024