

**Ceiling unit**  
**Novy Pureline Pro 120 cm**  
**Stainless steel**



### Energy label

|                                                  |      |
|--------------------------------------------------|------|
| ▪ Energy Efficiency class (EELhood)              | A    |
| ▪ Annual Energy Consumption (kWh/year) (AEChood) | 41,4 |
| ▪ Fluid Dynamic Efficiency class (FDEhood)       | A    |
| ▪ Lighting Efficiency class (LEhood)             | C    |
| ▪ Grease Filtering Efficiency class (GFEhood)    | D    |

### Functions & features

|                                            |                |
|--------------------------------------------|----------------|
| ▪ Motor                                    | Integrated     |
| ▪ Sound absorber                           | Integrated     |
| ▪ Recirculation                            | Optional       |
| ▪ InTouch function                         | Standard       |
| ▪ Auto stop                                | ▪              |
| ▪ Delayed switch off (minutes)             | 10             |
| ▪ Grease filter                            | 6830020        |
| ▪ Number of grease filters                 | 2              |
| ▪ Grease filter cleaning indication        | ▪              |
| ▪ Recirculation filter cleaning indication | ▪              |
| ▪ Control method                           | Remote control |
| ▪ Novy Connect                             | Standard       |
| ▪ Number of speeds                         | 3 + power      |
| ▪ Automatic Power revert (minutes)         | 6              |

### Dimensions

|                                                           |                               |
|-----------------------------------------------------------|-------------------------------|
| ▪ Product dimensions (WxDxH) (mm)                         | 1168 x 508 x 319              |
| ▪ Height incl. mounting clamps (without motorbox) (mm)    | 133                           |
| ▪ Width flange (mm)                                       | 15                            |
| ▪ Dimensions cut-out opening (WxD) (mm)                   | 1145 x 485                    |
| ▪ Advised mounting height induction hobs (Hmin-Hmax) (mm) | 600 - 1600                    |
| ▪ Advised mounting height gas hobs (Hmin-Hmax) (mm)       | 650 - 1600                    |
| ▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm)   | 600 - 1600                    |
| ▪ Diameter outlet (mm)                                    | 150                           |
| ▪ Position exhaust                                        | Right, Left, Front, Back, Top |

### Lighting

|                                                 |           |
|-------------------------------------------------|-----------|
| ▪ Functional lighting type                      | Led strip |
| ▪ Functional light dimmable                     | ▪         |
| ▪ Soft-ON/OFF                                   | ▪         |
| ▪ Total energy consumption functional light (W) | 21        |
| ▪ Color functional light (K)                    | 2700-5000 |
| ▪ Ambient lighting type                         | Led strip |
| ▪ Total energy consumption ambient light (W)    | 21        |
| ▪ Color ambient light (K)                       | 2700-5000 |

## Airflow and noise level

---

|                                                                                                                 |           |
|-----------------------------------------------------------------------------------------------------------------|-----------|
| ▪ Free airflow (m³/h)                                                                                           | 975       |
| ▪ Airflow (m³/h) measured according to EN 61591                                                                 |           |
| ▪ Sound regulation according to DIN 45635-2                                                                     |           |
| ▪ Airflow duct out speed 1 (m³/h) / Max pressure duct out speed 1 (Pa)                                          | 262 / 98  |
| ▪ Airflow duct out speed 2 (m³/h) / Max pressure duct out speed 2 (Pa)                                          | 466 / 343 |
| ▪ Airflow duct out speed 3 (m³/h) / Max pressure duct out speed 3 (Pa)                                          | 617 / 391 |
| ▪ Airflow duct out max powerspeed (m³/h) (Qboost) / Max pressure duct out max powerspeed (Pa)                   | 714 / 391 |
| ▪ Sound pressure duct out speed 1 (dB(A)) / Sound power duct out speed 1 (dB(A))                                | 27 / 39   |
| ▪ Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 2 (dB(A))                                | 40 / 52   |
| ▪ Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 3 (dB(A))                                | 46 / 59   |
| ▪ Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct out at max powerspeed (dB(A)) (LWAboost) | 49 / 62   |

## Technical specifications

---

|                                               |         |
|-----------------------------------------------|---------|
| ▪ Maximum power (W)                           | 230     |
| ▪ Voltage appliance (V)                       | 220-240 |
| ▪ Frequency (Hz)                              | 50-60   |
| ▪ Power consumption in stand-by-mode (Ps) (W) | 0,48    |
| ▪ Net weight (kg)                             | 22,7    |
| ▪ Length power supply cable (m)               | 1,2     |

Accessories

Recirculation box



841400

Exhaust box with monoblock filter



842400

Exhaust box with monoblock filter



843400

Exhaust box with monoblock filter



7931400

Exhaust box with monoblock filter



7932400

Exhaust box with monoblock filter



7933400

Recirculation box with monoblock filter

