

S-SERIES



SYNESSO QUALITY AND CONTROL WITH MORE ACCESS AND APPROACHABILITY

The S-Series continues the legacy of defining Synesso's craft. It's a low-profile, auto volumetric machine designed for cafes who need intuitive use with premium build quality and long service intervals.

Our auto-volumetric controls allow espresso parameter fine-tuning, so that daily users can rely on consistent results in the cup.

Adjustable auto-preinfusion combined with volumetric recipes means that baristas can engage with guests and provide a more enjoyable coffee experience, without needing constant attention on the extraction.

The low-profile design of the S-Series fosters an approachable atmosphere on any counter.



KEY ELEMENTS

- Workflow in mind: *new* easily removable drip tray with a deeper workspace.
- One-tap controls for both delicious espresso and our *new* one-tap auto-back flush.
- Connect with your customers over a low-profile with pre-set recipes: now up to 4 recipes per grouphead!
- Industrial components at an accessible price point.
- Industry leading design – now with a refreshed aesthetic with black screws and a redesigned back panel.
- Easily adjust preinfusion or recipes on the fly with the handheld controller.
- Consistently prepare premium espresso via independent brew-boilers and hand-bent copper tubing.
- Available in modern stock colors: matte Synesso White or matte Synesso Black
- Rainbow of classic RAL custom color options. Pair with a curated woodkit to complement your vibe!

ELECTRICAL

STEAM

BREW

	Voltage, Single Phase	Amps, Max Draw	Cord Plug Rating, Amps (UL)	Watts per Element	Total Wattage	Tank Capacity, Liters	Watts per Element	Total Wattage	Tank Capacity, Liters
2 Group	220v	28	30	2000 x 2	4000	7.7	700 x 2	1400	1.9 x 2
3 Group	220v	36	50	2500 x 2	5000	12.3	700 x 3	2100	1.9 x 3

ON THE COUNTER DIMENSIONS

SHIPPING DIMENSIONS

	Height	Width	Depth	Weight	Weight	Height	Width	Depth
2 Group	17.3" (445mm)	27.6" (702mm)	24" (610mm)	152lb (69kg)	247lb (112kg)	33" (838mm)	36" (914mm)	30" (762mm)
3 Group	17.3" (445mm)	37" (940mm)	24" (610mm)	225lb (102kg)	320lb (145kg)	33" (838mm)	46" (1168mm)	30" (762mm)

PLUMBING

Drain within 4' with a 1/2" air gap required

Direct Connection (Compression)

3/8in OD



Certified by Intertek (ETL) for Sanitation to NSF / ANSI 4

Certified by Intertek (ETL) for Electrical Safety to ANSI / UL 197

Certified by Intertek (ETL) for Electrical Safety to CSA C22.2 No. 109



C-Tick Compliant (By request)

CE Compliant (By request)