O8631V
UNIVERSAL ADJUSTABLE TRAY RACK
for 12”x20” Pans and 18”x26” Trays



O8631V

Model Number	Tray Capacity[1]		Tray Slide Spacing*		Overall Dimensions						Caster Diameter		Shipping Weight	
					Height		Depth		Width					
	18”x26”	12”x20”	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kgs
☐ O8631V	12	24	$4^{1}/_{2}$	114	64	1626	26	660	24	622	5	127	86	39

*adjustable on 1-1/2” increments

[1]see below for additional tray/pan types

CONSTRUCTION... Heavy gauge aluminum, fully reinforced with horizontal stabilizing bar to prevent buckling. Top, bottom and corner reifocements are welded to upright channels which are, in turn, welded to the base frame. Entire base frame and bolster pads are welded to form a solid one piece unit.

CABINET MATERIAL... Extruded tube 1-1/4” x 1-1/2” with 16/15” leg x .070 wall thickness on tube and .125 on leg. Upright leg is notched on 1-1/2” centers to accept universal stepped tray slide.

ANGLE SLIDES... stepped type; 2” x 6-3/16” x .100 thick. Bottom guides welded in place for support. Removable and adjustable on 1-1/2” centers. Standard spacing at 4-1/2” centers. Accommodate a wide variety of trays and pans, from 20” in width to 26” in length, including:
10”x20” roast and bake pans
20”x22” roast and bake pans
18”x26” roasting pans
18”x26” bun pans
12”x20” steam table pans
1/1 gastronorm pans
2/1 gastronorm pans
15”x20” service trays
20”x20” glass racks

CASTERS... Four 5” platform type swivel casters.

ACCESSORIES/OPTIONS...
- ☐ Caster locks (2)
- ☐ Corner bumpers (4)
- ☐ Pan stop
- ☐ Perimeter bumper
- ☐ Vertical bumpers

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

Printed in U.S.A. J35 0609
Carter-Hoffmann is a trademark of Carter-Hoffmann LLC

O1838C
LIP LOADED BUN PAN RACK
for 18” x 26” Trays



O1838C

Model Number	Tray Capacity[1]	Tray Slide Spacing		Overall Dimensions Height		Depth		Width		Caster Diameter		Shipping Weight	
	18”x26”	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kgs
☐ O1838C	38	$1\frac{1}{2}$	38	$69\frac{3}{4}$	1772	26	660	$20\frac{3}{8}$	517	5	127	56	25

[1]lip-loaded

CONSTRUCTION... All welded, heavy-duty, high tensile, type 6463-T5 alloy extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling.

CABINET MATERIAL... Vertical and horizontal frame members are 1” x 1” x .070 extruded aluminum tubing. Corner gussets of 1-1/2” x 1-1/2” x 5/8” thick angle are welded to the inside angles (bottom side) where horizontal cross bracing meets vertical uprights.

CHANNEL SLIDES... Slides are 3/4” x 1-9/16” channel slides welded to frame. Accept 18”x26” lip loaded bun pans on 1-1/2” centers.

CASTERS... Four 5” diameter platform casters. All swivel with sealed ball bearing. Non-marking polyurethane.

ACCESSORIES/OPTIONS...
- ☐ Solid base
- ☐ Corner bumpers (4)
- ☐ Caster locks (2) for 5” platform casters
- ☐ Perimeter bumper
- ☐ Pan stop
- ☐ Vertical bumpers

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

Printed in U.S.A. J35 0609
Carter-Hoffmann is a trademark of Carter-Hoffmann LLC