



**IMC VENTUS V60 BOTTLE COOLER [FRONT LOAD] - GLASS DOOR - BLACK PAINTED FRAME - H 850 MM - W 600 MM - R290**

**MODEL: F76/151/B**



**Ventus**

**PRODUCT OPTIONS AND ACCESSORIES**

- S76/048 Perforated Shelf - for V60 - 500D
- A12/091/Z1 Wire Shelf - Chrome - for M60 Bottle Cooler

**PRODUCT FEATURES**

- Reduced 850mm height
- Wide range of options available to customise your bottle cooler, ensure a perfect fit in any bar.
- Elegant, flexible storage for up to 78 bottles
- Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times.
- Electronic temperature control keeps drinks at the perfect serving temperature
- Energy efficient EcoSmart controller - at the touch of a button, put the bottle cooler into its most economical state until next required
- Sleek stainless steel interior and LED lighting to enhance display
- Single double-glazed lockable door for enhanced security
- UK 3 pin plug allows users to simply plug in and switch on

The V60 provides flexible storage of up to 78 (330ml) bottles. The polished stainless steel interior and LED lighting enhance display, while the black painted exterior cabinet blends seamlessly into any bar setting.

Its electronic temperature controller, supported by an auto defrost function, provides precise monitoring, ensuring drinks are kept at perfect serving temperature. In addition, the energy-saving EcoSmart controller allows users to hold the bottle cooler in its most economical state, until it is required, and an energy-efficient forced air cooling system delivers rapid temperature pull down to keep pace with demand in the busiest of bars.

A/A FILE NUMBER:

ITEM NUMBER:



# IMC VENTUS V60 BOTTLE COOLER [FRONT LOAD] - GLASS DOOR - BLACK PAINTED FRAME - H 850 MM - W 600 MM - R290

## MODEL: F76/151/B

### WEIGHTS & DIMENSIONS

|        |         |
|--------|---------|
| Width  | 600 mil |
| Depth  | 500 mil |
| Height | 850 mil |
| Weight | 60 kg   |

### SHIPPING DETAILS

|                          |                                |
|--------------------------|--------------------------------|
| Ship Width               | 67 cm                          |
| Ship Depth               | 58 cm                          |
| Ship Height              | 106 cm                         |
| Ship Weight              | 64 kg                          |
| Ship Method              | Small Parcel (FedEx, UPS, DHL) |
| Shipping Package Type    | Pieces                         |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM        |
| Quick Ship Product       | No                             |

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

|                           |          |                                      |               |
|---------------------------|----------|--------------------------------------|---------------|
| Primary Energy Type       | Electric | Electrical Plug Type                 | UK 3-Pin Plug |
| Electrical Total Amperage | 1.64 A   | Number of Electrical Plugs           | 1             |
| Electrical Volts          | 240V     | Electrical Connection Type           | Cord and Plug |
| Electrical Total Wattage  | 393 W    | Number of Electrical Conductor Wires | 1             |
| Electrical Kilowatts      | 0.393 kW | Dedicated Circuit Required           | No            |
| Electrical Phase          | 1-Phase  | Electrical Remarks                   | Single        |

### ADDITIONAL SPECIFICATIONS

|                        |                               |                           |       |
|------------------------|-------------------------------|---------------------------|-------|
| Application Type       | Undercounter                  | Insulated                 | Yes   |
| Capacity: Bottles      | 78                            | Number of Shelf Positions | 29    |
| Capacity (Volume)      | 119 l                         | Number of Shelves         | 2     |
| Construction Materials | Stainless Steel               | Refrigerant Type          | R-290 |
| Control Type           | Digital Touch Pad, Electronic | Type of Lighting          | LED   |
| Defrost Method         | Automatic                     | Temperature Maximum       | 6 °C  |
|                        |                               | Temperature Minimum       | 2 °C  |

### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

