



The IMC Cirrus 700L Upright Fridge delivers reliable, high-capacity refrigerated storage for professional kitchens. Designed to accommodate GN 2/1 gastronorm containers, it features ventilated cooling for consistent temperatures, electronic controls for precise temperature management and a durable 304 stainless steel interior and exterior. Automatic defrost and condensate evaporation reduce maintenance, while R290 refrigerant and high-performance insulation improve energy efficiency. Supplied on castors with a reversible self-closing door and flexible shelf positions, it combines practicality with dependable performance.

PRODUCT FEATURES

- 700L capacity – High-volume refrigerated storage for busy commercial kitchens.
- GN 2/1 compatible – Designed to accommodate standard gastronorm containers for maximum flexibility.
- Electronic temperature control – Precise temperature management for reliable food storage.
- Ventilated cooling – Even air circulation ensures consistent temperatures throughout.
- 24 shelf positions – Flexible storage to suit a wide range of products.
- 304 stainless steel interior & exterior – Durable, hygienic and easy to clean.
- Rounded internal corners – Improves hygiene with quicker, easier cleaning.
- Automatic defrost – Prevents ice build-up and maintains cooling performance.
- Automatic condensate evaporation – Eliminates the need for manual water disposal.
- Energy-efficient natural refrigerant with low environmental impact.
- High-performance insulation – Retains temperature efficiently to reduce energy consumption.
- Reversible self-closing door – Flexible installation while reducing cold air loss.
- Supplied on castors – Easy to move for cleaning and maintenance.

AIA FILE NUMBER:

ITEM NUMBER:



WEIGHTS & DIMENSIONS

Product Width	683 mm
Product Depth	800 mm
Product Height	2,090 mm
Product Dimensions (WxDxH) (mm)	683 Millimeter X 800 Millimeter X 2090 Millimeter

SHIPPING DETAILS

Ship Width	74 cm
Ship Depth	85 cm
Ship Height	228 cm
Ship Weight	115 kg
Shipping Package Type	Pieces

PRODUCT CERTIFICATION ICONS



ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	230V
Electrical Volts Icon	230V
Electrical Phase Icon	1PH

ADDITIONAL TECHNICAL SPECIFICATIONS

Capacity (Volume)	700
Door Material	Solid
Number of Shelves	3
Temperature Minimum	-2

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

