



The IMC Cirrus 275L Counter Fridge delivers reliable refrigerated storage in a compact undercounter design. Compatible with GN 1/1 gastronorm containers, it features ventilated cooling for even temperature distribution and electronic controls with digital display and alarms for precise temperature management between -2°C and +8°C. A durable 304 stainless steel interior, 441 stainless steel exterior, automatic defrost, automatic condensate evaporation, R290 refrigerant and high-performance cyclopentane insulation ensure efficient, dependable operation. Supplied on lockable castors with two GN 1/1 stainless steel shelves.

PRODUCT FEATURES

- 275L capacity – Compact refrigerated storage ideal for commercial kitchens where space is at a premium.
- GN 1/1 compatible – Designed to accommodate standard gastronorm containers for efficient food storage.
- Electronic temperature control – Digital controller with alarms ensures precise temperature management between -2°C and +8°C.
- Ventilated cooling system – Even air circulation maintains consistent temperatures throughout the cabinet.
- Automatic defrost & condensate evaporation – Reduces maintenance while maintaining optimum refrigeration performance.
- Environmentally friendly refrigerant delivering efficient cooling with a low global warming impact.
- High-performance cyclopentane insulation – 50mm CFC and HCFC-free insulation improves temperature retention and energy efficiency.
- 304 stainless steel interior – Hygienic, durable and easy to clean for demanding commercial environments.
- 441 stainless steel exterior – Robust construction designed to withstand everyday commercial use.
- Rounded internal corners – Enhances hygiene by making the interior quicker and easier to clean.
- Two GN 1/1 stainless steel shelves – Durable shelving for organised, flexible refrigerated storage.

AIA FILE NUMBER:

ITEM NUMBER:



WEIGHTS & DIMENSIONS

Product Width	1,315 mm
Product Depth	700 mm
Product Height	867 mm
Product Dimensions (WxDxH) (mm)	1315 Millimeter X 700 Millimeter X 867 Millimeter

SHIPPING DETAILS

Ship Width	135 cm
Ship Depth	74 cm
Ship Height	100 cm
Ship Weight	120 kg
Shipping Package Type	Pieces

PRODUCT CERTIFICATION ICONS



ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	230V
Electrical Volts Icon	230V
Electrical Phase Icon	1PH

ADDITIONAL TECHNICAL SPECIFICATIONS

Capacity (Volume)	275
Door Material	Solid
Number of Shelves	2
Temperature Minimum	-2

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

