



SILVERLINK 600

#### PRODUCT OPTIONS AND ACCESSORIES

- CC7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm
- HC7 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW
- HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW

Do you need to safely hold sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature? This Silverlink 600 Electric Wet Heat Bain Marie does just that. Perfect for takeaways, restaurants and mobile caterers, the unit, which can also be used as a dry bain marie, is designed to plug in and play, so you'll be serving delicious dishes in no time. With 6 x 1/3 150mm deep gastronorms and lids included, the unit also comes with an adjustable temperature control.

#### PRODUCT FEATURES

- Wet heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 6 x 1/3 150mm deep gastronorms with lids are included
- This wet unit can also be used as a dry bain marie
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & pre-cooked foods
- Adjustable temperature control

**WEIGHTS & DIMENSIONS**

Width	750 mil
Depth	600 mil
Height	290 mil
Weight	22.4 kg

**SHIPPING DETAILS**

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	49.5 cm
Ship Weight	24.64 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

**WATER, PLUMBING, AND DRAINAGE SPECS**

Water Line Required	No
Drain Line Required	No
Drain Location	Front Mounted

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	8.7 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	2000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	2 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

**ADDITIONAL SPECIFICATIONS**

Construction Materials	Stainless Steel	Mounting Position	Top Mount Drop-In
Control Type	Rotary Control Knob	Number of Wells	6
Gastronorm Capacity	3 x GN1/6, 6 x GN1/4	Ventless Cooking Technology	No
Hot Food Well Application Type	Wet	Waterless	No
Insulated	No	Well Shape	Rectangle
Modular	Yes		

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

TECHNICAL DRAWING

