



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- BA96 BASKET SPUN DFSMALL
- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

PRODUCT FEATURES

- Two independently operated fryer tanks for greater versatility, delivering 24kg of chips per hour
- Front mounted controls for safety
- Hinged elements to give easy access during cleaning
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Fail-safe top temperature cut out ensures safe operation.
- Fully moulded 304 stainless steel tank and heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil
- Supplied with two cables and two plugs for easy installation

Fry perfectly crispy and fluffy chips every time with the Silverlink 600 Electric Twin Tank Counter Top Fryer. Ideal for mobile operations and a range of venues such as cafes, pubs and restaurants, the fryer has two independently operated fryer tanks for greater versatility, combined with a power that can deliver 24kg of chips per hour. Sturdy stainless steel means it's built to last, hinged elements give easy access during cleaning, and you're in control via the accurate thermostat throughout the cooking process. Then there's the innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK ELECTRIC COUNTER-TOP TWIN TANK FRYER - 2 BASKETS - W 600 MM - 2 X 3.0 KW

MODEL: DF66

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	600 mil
Height	330 mil
Weight	22 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	49.5 cm
Ship Weight	24.2 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Amps Per Conductor	2 x 13.0	Number of Electrical Plugs	2
Electrical Total Amperage	26 A	Electrical Connection Type	Cord and Plug
Electrical Volts	230V	Number of Electrical Conductor Wires	2
Electrical Total Wattage	6000 W	Dedicated Circuit Required	No
Electrical Kilowatts	6 kW	Electrical Remarks	Single
Electrical Phase	1-Phase		

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Vats (batteries)	2
Basket Lift Type	Not Applicable	Total Oil Capacity (volume)	15 l
Construction Materials	Stainless Steel	Oil Reclamation	No
Control Type	Rotary Control Knob	Oil Temperature Control	Mechanical
Food Production Rate	16kg chips-12mm	Pumped Oil Filtration	No
	[frozen], 24kg	Vat 1 Oil Capacity (volume)	7.5 l
	chips-12mm[chilled]	Vat 2 Oil Capacity (volume)	7.5 l
	per hour	Ventless Cooking Technology	No
Fryer Type	Open Pot	Split Pot	Yes
Integrated Filtration	No	Temperature Maximum	190 °C
Number of Baskets	2		

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 24, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

