



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SB4 450 GRIDDLE SPLASHB
- CC4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 450 mm
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm
- HC4 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 450 mm - 0.5 kW
- HCL4 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 450 mm - 0.5 kW

PRODUCT FEATURES

- Hard wearing 12 mm thick machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- Plug and play for an easy installation

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and excellent heat retention, while the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results. The griddle, perfect for cafes, pubs and restaurants, is designed to plug in and play, so you'll be cooking mouthwatering dishes in no time.

WEIGHTS & DIMENSIONS

Width	450 mil
Depth	600 mil
Height	330 mil
Weight	30.9 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	55 cm
Ship Height	63.5 cm
Ship Weight	33.99 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	11.7 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	2700 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	2.7 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number of Heating Zones	2
Control Type	Rotary Control Knob	Plate Thickness	12 mm
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	412 mm	Ventless Cooking Technology	No
Cooking Plate Finish Material Type	Polished Steel	Temperature Maximum	250 °C
Lower Platen Surface Type	Smooth	Temperature Minimum	50 °C
Number Of Controls	2	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

