



**SILVERLINK 600**

**PRODUCT OPTIONS AND ACCESSORIES**

- SB6 600 GRIDDLE SPLASHB
- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

**PRODUCT FEATURES**

- Extra powered element for maximum output for a busy kitchen
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Hard wearing 12 mm thick machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. It comes with two separately controlled heat zones which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. The griddle also features an extra powered element for maximum output in busy kitchens. It's perfect for cafes, pubs and restaurants.

AIA FILE NUMBER:

ITEM NUMBER:

**WEIGHTS & DIMENSIONS**

Width	600 mil
Depth	620 mil
Height	330 mil
Weight	39.7 kg

**SHIPPING DETAILS**

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	43.67 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

**WATER, PLUMBING, AND DRAINAGE SPECS**

Water Line Required	No
Drain Line Required	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Type	Electric
Electrical Amps Per Conductor	Single Phase 24.3/Three Phase L1=12.2; L2=12.2; L3=N/
Electrical Total Amperage	24.3 A
Electrical Volts	230-400V
Electrical Total Wattage	5600 W

Electrical Kilowatts	5.6 kW
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	Yes
Electrical Remarks	Single, Three

**ADDITIONAL SPECIFICATIONS**

Control Type	Rotary Control Knob
Cooking Area Plate Depth	405 mm
Cooking Area Plate Width	562 mm
Cooking Plate Finish Material Type	Polished Steel
Lower Platen Surface Type	Smooth
Number Of Controls	2

Number of Heating Zones	2
Plate Shape	Rectangle
Plate Thickness	12 mm
Temperature Maximum	250 °C
Temperature Minimum	50 °C
Thermostat Element Location	Under Plate Mount

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

TECHNICAL DRAWING

