



**SILVERLINK 600**

#### PRODUCT OPTIONS AND ACCESSORIES

- SB7 750 GRIDDLE SPLASHB
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm

#### PRODUCT FEATURES

- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- Front mounted control for easy of use during cooking
- Piezo ignition for easy lighting of the burners
- Flame failure device for maximum safety



# LINCAT SILVERLINK PROPANE GAS COUNTER-TOP GRIDDLE - STEEL PLATE - W 750 MM - 8.0 KW

## MODEL: GS7/P

### WEIGHTS & DIMENSIONS

Width	750 mil
Depth	650 mil
Height	415 mil
Weight	54 kg

### SHIPPING DETAILS

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	59.4 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Type	Gas
Electrical Kilowatts	8 kW
Gas Type	Propane
Gas Total BTUs	27296 BTU
Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	25 mBar
Gas Consumption at Max Use Per Hour	0.57 m <sup>3</sup>
Total Heat Input at Max Use	8 kW, 25600 BTU per hour

### ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number Of Controls	2
Control Type	Mechanical	Plate Thickness	12 mm
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	712 mm	Ventless Cooking Technology	No
Cooking Plate Finish Material Type	Polished Steel	Temperature Maximum	250 °C
Lower Platen Surface Type	Smooth	Temperature Minimum	50 °C
Number of Burners	2	Thermostat Element Location	Under Plate Mount

### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

