



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SB9 900 GRIDDLE SPLASHBACK - GS9 ONLY
- SLS9 Lincat Silverlink 600 Free-standing Floor Stand - for units W 900 mm
- HCL9 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 900 mm - 1.0 kW

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and an easy to clean surface, and also features two separately controlled heat zones, which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. The two-zone system is designed to give you maximum flexibility during service. The griddle, perfect for cafes, pubs and restaurants, is also thermostatically controlled to give accurate temperatures during the cooking process for consistent results.

PRODUCT FEATURES

- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- 2 cooking zone to give maximum flexibility during service
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Front mounted control for easy of use during cooking

WEIGHTS & DIMENSIONS

Width	900 mil
Depth	620 mil
Height	330 mil
Weight	60.9 kg

SHIPPING DETAILS

Ship Width	101.5 cm
Ship Depth	72 cm
Ship Height	59.5 cm
Ship Weight	66.99 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Amps Per Conductor	Single Phase 37.4/Three Phase L1=12.1; L2=12.1; L3=13.1	Number of Electrical Plugs	Not Applicable
Electrical Total Amperage	37.4 A	Electrical Connection Type	Direct Hardwired
Electrical Volts	230-400V	Number of Electrical Conductor Wires	1
Electrical Total Wattage	8600 W	Dedicated Circuit Required	Yes
Electrical Kilowatts	8.6 kW	Electrical Remarks	Single, Three

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number of Heating Zones	2
Control Type	Rotary Control Knob	Plate Thickness	12 mm
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	862 mm	Ventless Cooking Technology	No
Cooking Plate Finish Material Type	Polished Steel	Temperature Maximum	250 °C
Lower Platen Surface Type	Smooth	Temperature Minimum	50 °C
Number Of Controls	2	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

