

LINCAT SILVERLINK NATURAL GAS FREE-STANDING TWIN TANK FRYER - 2 BASKETS - W 600 MM - 24.0 KW

MODEL: J10/N



SILVERLINK 600

Deliver perfectly crisp on the outside and fluffy on the inside chips time after time with the Silverlink 600 Free Standing Gas Fryer. Twin tanks and twin baskets means you have the flexibility to cook different foods or loads simultaneously, while delivering 46kg of chips an hour. Ideal for cafes, pubs and restaurants, the fryer features piezo ignition for easy lighting and heavy duty nickel plated baskets for the most demanding of operations. You're in control via the accurate thermostat throughout the entire cooking process. Then there's the innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money.

PRODUCT FEATURES

- Double tank twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 46kg of chips an hour
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris gives cleaner cooking results and saves money by prolonging the life of the oil
- · Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Internal drain off tap for easy removal of cooking oil







LINCAT SILVERLINK NATURAL GAS FREE-STANDING TWIN TANK FRYER - 2 BASKETS - W 600 MM - 24.0 KW

MODEL: J10/N

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	690 mil
Height	1060 mil
Weight	73.7 kg

SHIPPING DETAILS	
Ship Width	81.3 cm
Ship Depth	68.5 cm
Ship Height	122 cm
Ship Weight	81.07 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS	
Primary Energy Type	Gas
Electrical Kilowatts	24 kW
Electrical Plug Type	Not Applicable
Number of Electrical Plugs	Not Applicable
Electrical Connection Type	Direct Hardwired
Gas Type	Natural Gas

Gas Total BTUs	81880 BTU
Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	16.3 mBar
Gas Consumption at Max Use Per Hour	2.29 m ³
Total Heat Input at Max Use	22.79 kW, 74000 BTU per hour

ADDITIONAL SPECIFICATIONS	
Auto Oil Top-Off	No
Basket Lift Type	Not Applicable
Construction Materials	Stainless Steel
Control Type	Mechanical
Food Production Rate	36kg chips -12mm [frozen], 46kg chips - 12mm [chilled] per hour
Fryer Type	Open Pot
Integrated Filtration	No
Number of Baskets	2

Number of Burners	4
Number of Vats (batteries)	2
Total Oil Capacity (volume)	24 l
Oil Reclamation	No
Oil Temperature Control	Mechanical
Pumped Oil Filtration	No
Vat 1 Oil Capacity (volume)	12
Vat 2 Oil Capacity (volume)	12
Ventless Cooking Technology	No
Split Pot	Yes
Temperature Maximum	190 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 24, 2025







MODEL: J10/N


BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 24, 2025

