



Opus 800

Designed for quality cooking at speed, the Opus 800 Electric Chrome Griddle heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system. Not only is heat transferred more efficiently than with a standard griddle, but the precise thermostatic control up to 300°C means that you're always in control, whether your cooking meat, eggs or vegetables. Perfect for any busy commercial kitchen, the chrome griddle comes with two separately controlled heat zones, which allow for the versatility of operating either zone independently when cooking two separate meals simultaneously.

PRODUCT OPTIONS AND ACCESSORIES

- OA8914/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 900 mm
- OA8914 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 900 mm
- OA8973/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 900 mm
- OA8973 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 900 mm
- LK11 OPUS 800 LONG LEG KIT

PRODUCT FEATURES

- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Precise thermostatic control up to 300°C for consistent results and economical operation

WEIGHTS & DIMENSIONS

Width	900 mil
Depth	800 mil
Height	428 mil
Weight	118 kg

SHIPPING DETAILS

Ship Width	100 cm
Ship Depth	85 cm
Ship Height	64 cm
Ship Weight	129.8 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Amps Per Conductor	Single Phase 52.2/Three Phase L1=17.4; L2=17.4; L3=17.4	Number of Electrical Plugs	Not Applicable
Electrical Total Amperage	52.2 A	Electrical Connection Type	Direct Hardwired
Electrical Volts	230-400V	Number of Electrical Conductor Wires	1
Electrical Total Wattage	12000 W	Dedicated Circuit Required	Yes
Electrical Kilowatts	12 kW	Electrical Remarks	Single, Three

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number of Heating Zones	2
Control Type	Rotary Control Knob	Plate Thickness	15 mm
Cooking Area Plate Depth	890 mm	Plate Shape	Rectangle
Cooking Area Plate Width	600 mm	Ventless Cooking Technology	No
Cooking Plate Finish Material Type	Chrome Plated	Temperature Maximum	300 °C
Lower Platen Surface Type	Smooth	Temperature Minimum	90 °C
Number Of Controls	2	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

