



*Opus* **800**

Cook flavoursome and succulent food up to three times faster than with a traditional griddle with the Opus 800 Clam Griddle with one flat and one ribbed upper plate. The method of cooking from above and below ensures that meat doesn't shrink and the juices and flavour remains locked in, and the ribbed plate adds attractive branding marks to make food look even more appetizing. Perfect for cooking steaks, burgers, chicken and other meat products, the Clam Griddle is ideal for any busy commercial kitchen. It comes with a precise thermostatic control for consistent results, while a digital timer on each clam plate ensures that you're in control.

#### PRODUCT OPTIONS AND ACCESSORIES

- OA8960 3 POSITION HEIGHT ADJUSTER 10-20-30 - OPUS 800
- OA8956/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 800 mm
- OA8956 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 800 mm
- OA8974/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 800 mm
- OA8974 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 800 mm
- TFS01 TEFLON SHEET - CLAM GRIDDLE

#### PRODUCT FEATURES

- Heat from above and below locks in flavour and reduces shrinkage of meat
- Cook food up to three times as quickly as a standard griddle
- Ribbed plate gives food attractive brand marks
- Digital timer on each clam plate ensures repeatable results
- Precise thermostatic control for consistent results and economical operation



# LINCAT OPUS ELECTRIC COUNTER-TOP CLAM GRIDDLE - 1 X FLAT PLATE; 1 X RIBBED PLATE - W 800 MM - 17.2 KW

## MODEL: OE8210/FR

### WEIGHTS & DIMENSIONS

Width	800 mil
Depth	800 mil
Height	542 mil
Weight	155 kg

### SHIPPING DETAILS

Ship Width	90 cm
Ship Depth	85 cm
Ship Height	72 cm
Ship Weight	170.5 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Type	Electric	Electrical Phase	3-Phase
Electrical Amps Per Conductor	L1=28.0; L2=28.0; L3=18.0	Electrical Plug Type	Hardwired
Electrical Total Amperage	74 A	Number of Electrical Plugs	Not Applicable
Electrical Volts	400V	Electrical Connection Type	Direct Hardwired
Electrical Total Wattage	17200 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	17.2 kW	Dedicated Circuit Required	Yes
		Electrical Remarks	Three

### ADDITIONAL SPECIFICATIONS

Bottom Plate Energy Type	Electric	Number of Individual Upper Platens	2
Construction Materials	Stainless Steel	Plate Thickness	15 mm
Control Type	Mechanical	Plate Shape	Rectangle
Cooking Plate Finish Material Type	Polished Steel	Ventless Cooking Technology	No
Food Production Rate	280 x 113g burgers [4oz] burgers [frozen] per hour	Temperature Maximum	250 °C
		Temperature Minimum	50 °C
Lower Platen Surface Type	Smooth	Thermostat Element Location	Lower Plate & Upper Platen Mounted
Upper Platen Surface Type	Smooth and Grooved	Upper Platen Energy Type	Electric
Number of Heating Zones	2	Upper Platen Type	Contact

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
March 24, 2025

#### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

#### TECHNICAL DRAWING

