

LINCAT OPUS PROPANE GAS FREE-STANDING SOLID TOP OVEN RANGE [DROP-DOWN DOOR] - W 900 MM - 19.0 KW

MODEL: OG8005/P/DD



Designed for ultimate accuracy and versatility, the Opus 800 Solid Top Range with Cast Iron Plate provides chefs with more flexibility when it comes to the size and number of pans used. There's a profiled underside of the cast iron top for optimum heat circulation, while the powerful dual burner produces consistent heat gradient throughout the plate. Ideal for any busy commercial kitchen, the powerful oven has a large 4 x GN1/1 capacity.

Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- LK06 OPUS 800 LEG KIT
- OA8980 SPLASHBACK/SHELF OG8005

PRODUCT FEATURES

- Ultimate flexibility use the smallest of pans to the largest of stock pots
 Use the central area for rapid boiling and outer areas for simmering and holding
- Powerful 10kW dual Burner produces consistent heat gradient throughout the plate
- Profiled underside of cast iron top for optimum heat circulation
- Low flue to allow use of the complete hob top
- Powerful 9.5kW oven







LINCAT OPUS PROPANE GAS FREE-STANDING SOLID TOP OVEN RANGE [DROP-DOWN DOOR] - W 900 MM - 19.0 KW

MODEL: OG8005/P/DD

WEIGHTS & DIMENSIONS	
Width	900 mm
Depth	800 mm
Height	900 mm
Weight	154.5 kg

SHIPPING DETAILS	
Ship Width	100 cm
Ship Depth	800 cm
Ship Height	103 cm
Ship Weight	169.95 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS				
Primary Energy Type	Gas	Gas Inlet Size	0.75 in	
Electrical Kilowatts	19 kW	Gas Inlet Pressure Required	37 mBar	
Dedicated Circuit Required	No	Gas Consumption at Max Use Per Hour	1.36 m ³	
Gas Type	Propane	Total Heat Input at Max Use	19 kW, 64830 BTU per	
Gas Total BTUs	64830 BTU	Total fleat illput at Max Ose	hour	

ADDITIONAL SPECIFICATIONS			
Construction Materials	Stainless Steel	Open or Sealed Burners	Sealed
Control Type	Mechanical	Oven Power Rating	9 kW
Cooking Plate Finish Material Type	Cast Iron Plate	Oven Temperature Minimum	120 °C
Exterior Trim Finish Color	Stainless Steel	Oven Temperature Maximum	260 °C
Gastronorm Capacity	4 x GN1/1	Shelf Depth	512 mm
High Altitude Kit Available	No	Shelf Width	710 mm
Number of Heating Zones	1_	Ventless Cooking Technology	No
Number of Hot Top Burners	1_	Cooking Equipment	Hot Plate
Number of Shelf Positions	4	BTUs Per Burner	9 KW
Number of Shelves	2		

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 25, 2025





LINCAT OPUS PROPANE GAS FREE-STANDING SOLID TOP OVEN RANGE [DROP-DOWN DOOR] - W 900 MM - 19.0 KW

MODEL: OG8005/P/DD

SELECT COOKING EQUIPMENT	NUMBER OF		POWER RATING	ARRANGE- MENT	WIDTH	DEPTH
Hot Plate		1		Center	900 mm	600 mm
SELECT BASE EQUIPMENT	NUMBER OF		CUBIC CAPACITY EACH	WIDTH	DEPTH	HEIGHT
Standard Oven 1		1		715 mm	800 mm	405 mm

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 25, 2025








LINCAT OPUS PROPANE GAS FREE-STANDING SOLID TOP OVEN RANGE [DROP-DOWN DOOR] - W 900 MM - 19.0 KW

MODEL: OG8005/P/DD

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 25, 2025

