



Opus **800**

PRODUCT OPTIONS AND ACCESSORIES

- LK02 OPUS 350 LEG KIT
- OA8961 SPLASHGUARD VORTECH - OPUS 800

PRODUCT FEATURES

- 97% energy efficiency rating verified in independent BSI tests delivers substantially lower running costs and higher output
- Two stage filtration extends oil life by up to 75% and so reducing oil costs
- Oil can be filtered during or after service even whilst hot
- Convenient electronic ignition
- Externally fired heating gives easy access for cleaning tanks

Fry delicious food and save money and energy at the same time, with this Vortech High Efficiency Opus 800 Free Standing Fryer. Boasting a 97% energy efficiency rating verified in independent BSI tests, the fryer delivers substantially lower running costs and higher output than other fryers. It also comes with a two-stage filtration system which extends oil life by up to 75%, therefore saving you even more money. Designed to meet the needs of any busy commercial kitchen, the powerful, sturdy fryer comes with convenient electronic ignition and filters the oil so that it's ready to use again in less than five minutes.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT OPUS PROPANE GAS FREE-STANDING SINGLE TANK
FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 22.0

MODEL: OG8115/OP/P

WEIGHTS & DIMENSIONS

Width	400 mm
Depth	800 mil
Height	1070 mm
Weight	99.2 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	800 cm
Ship Height	122 cm
Ship Weight	109.12 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Gas	Dedicated Circuit Required	Yes
Electrical Total Amperage	4.9 A	Electrical Remarks	Single
Electrical Volts	230V	Gas Type	Propane
Electrical Total Wattage	100 W	Gas Total BTUs	75064 BTU
Electrical Kilowatts	22 kW	Gas Inlet Size	0.5 in
Electrical Phase	1-Phase	Gas Inlet Pressure Required	37 mBar
Electrical Plug Type	Hardwired	Gas Consumption at Max Use Per Hour	1.57 m ³
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	22 kW, 75064 BTU per hour
Electrical Connection Type	Direct Hardwired		
Number of Electrical Conductor Wires	1		



**LINCAT OPUS PROPANE GAS FREE-STANDING SINGLE TANK
FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 22.0**

MODEL: OG8115/OP/P

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Baskets	2
Basket Lift Type	Not Applicable	Number of Burners	2
Construction Materials	Stainless Steel	Number of Vats (batteries)	1
Control Type	Mechanical	Total Oil Capacity (volume)	16 l
Filter Media Type (if applicable)	2-Stage: Fine Tissue Filter and Stainless Steel Filter	Oil Reclamation	No
Food Production Rate	40kg chips - 12mm [frozen], 51kg chips - 12mm [chilled] per hour	Oil Temperature Control	Mechanical
Fryer Type	Open Pot	Pumped Oil Filtration	Yes
Integrated Filtration	Yes	Vat 1 Oil Capacity (volume)	16 l
		Ventless Cooking Technology	No
		Split Pot	No
		Temperature Maximum	190 °C

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

