



*Opus* 800

### PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- OA8914/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 900 mm
- OA8914 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 900 mm
- OA8973/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 900 mm
- OA8973 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 900 mm

### PRODUCT FEATURES

- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Convenient piezo ignition and pilot Burners for stand-by operation
- Flame failure protection

Designed for quality cooking at speed, the Opus 800 Gas Chrome Griddle heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system. Heat is transferred more efficiently than with a standard griddle, while the chrome griddle also comes with two separately controlled heat zones, which allow for the versatility of operating either zone independently when cooking two separate meals simultaneously. Perfect for any busy commercial kitchen, the griddle also comes with convenient piezo ignition, pilot burners for stand-by operation, and flame failure protection for added safety.

AIA FILE NUMBER:

ITEM NUMBER:

#### WEIGHTS & DIMENSIONS

|        |         |
|--------|---------|
| Width  | 900 mm  |
| Depth  | 800 mil |
| Height | 532 mm  |
| Weight | 108 kg  |

#### SHIPPING DETAILS

|                          |                         |
|--------------------------|-------------------------|
| Ship Width               | 100 cm                  |
| Ship Depth               | 800 cm                  |
| Ship Height              | 63 cm                   |
| Ship Weight              | 118.8 kg                |
| Ship Method              | LTL Common Carrier      |
| Shipping Package Type    | Pieces                  |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product       | No                      |

#### PRODUCT CERTIFICATIONS



#### ENERGY SPECS

|                                     |             |
|-------------------------------------|-------------|
| Primary Energy Type                 | Gas         |
| Electrical Kilowatts                | 23 kW       |
| Gas Type                            | Natural Gas |
| Gas Total BTUs                      | 78476 BTU   |
| Gas Inlet Size                      | 0.5 in      |
| Gas Inlet Pressure Required         | 20 mBar     |
| Gas Consumption at Max Use Per Hour | 2.19 m³     |
| Total Heat Input at Max Use         | 23 kW       |

#### ADDITIONAL SPECIFICATIONS

|                                    |                 |                             |                   |
|------------------------------------|-----------------|-----------------------------|-------------------|
| Construction Materials             | Stainless Steel | Number Of Controls          | 2                 |
| Control Type                       | Mechanical      | Plate Thickness             | 15 mm             |
| Cooking Area Plate Depth           | 600 mm          | Plate Shape                 | Rectangle         |
| Cooking Area Plate Width           | 590 mm          | Ventless Cooking Technology | No                |
| Cooking Plate Finish Material Type | Chrome Plated   | Temperature Maximum         | 280 °C            |
| Lower Platen Surface Type          | Smooth          | Temperature Minimum         | 90 °C             |
| Number of Burners                  | 2               | Thermostat Element Location | Under Plate Mount |

#### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

### TECHNICAL DRAWING

