



**PANTHER**

#### PRODUCT OPTIONS AND ACCESSORIES

- PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD
- PPB6 PPB6 - ADDITIONAL PUSHBAR

#### PRODUCT FEATURES

- 670mm depth allows access through narrow door openings also ideal to fit through narrow corridors
- Ideal for small restaurants, cafes and pubs, as well as nursing and care homes, where the easy transportation of plated meals to diners and residents is a necessity.
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 3 x 1/1 GN containers up to 150mm deep.
- Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads

#### WEIGHTS & DIMENSIONS

|        |          |
|--------|----------|
| Width  | 1205 mil |
| Depth  | 670 mil  |
| Height | 900 mil  |
| Weight | 87.5 kg  |

#### SHIPPING DETAILS

|                          |                         |
|--------------------------|-------------------------|
| Ship Width               | 120 cm                  |
| Ship Depth               | 80 cm                   |
| Ship Height              | 103 cm                  |
| Ship Weight              | 96.25 kg                |
| Ship Method              | LTL Common Carrier      |
| Shipping Package Type    | Pieces                  |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product       | No                      |

#### PRODUCT CERTIFICATIONS



#### ENERGY SPECS

|                           |          |                                      |               |
|---------------------------|----------|--------------------------------------|---------------|
| Primary Energy Type       | Electric | Electrical Plug Type                 | UK 3-Pin Plug |
| Electrical Total Amperage | 6.5 A    | Number of Electrical Plugs           | 1             |
| Electrical Volts          | 230V     | Electrical Connection Type           | Cord and Plug |
| Electrical Total Wattage  | 1500 W   | Number of Electrical Conductor Wires | 1             |
| Electrical Kilowatts      | 1.5 kW   | Dedicated Circuit Required           | No            |
| Electrical Phase          | 1-Phase  | Electrical Remarks                   | Single        |

#### ADDITIONAL SPECIFICATIONS

|                        |                               |                           |        |
|------------------------|-------------------------------|---------------------------|--------|
| Plate Diameter Maximum | 12.75 in                      | Number of Shelf Positions | 4      |
| Plate Diameter Minimum | 11.25 in                      | Number of Shelves         | 2      |
| Cart Style             | Plated Meals and Pans         | Plate Capacity            | 316    |
| Construction Materials | Stainless Steel               | Shelf Depth               | 512 mm |
| Control Type           | Digital Touch Pad, Electronic | Shelf Width               | 980 mm |
| Heating System         | Electric                      | Temperature Maximum       | 99 °C  |
| Number of Doors        | 2                             | Temperature Minimum       | 20 °C  |

#### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

#### TECHNICAL DRAWING

