



PANTHER

PRODUCT FEATURES

- Ideal for warming plates and for holding food safely and effectively at the desired temperatures
- Fully insulated for enhanced energy-efficiency
- Adjustable thermostatic control to meet food safety regulations
- Compact, space saving design

Are you looking for a unit to hold food safely and effectively at the perfect temperature? The compact Panther Light Duty Series Hot Cupboard, which can also be used for warming plates, comes fully insulated for enhanced energy-efficiency, while there's also an adjustable thermostatic control to meet food safety regulations. This model is ideal for smaller establishments where space is at a premium or where budgets are tight.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT PANTHER LIGHT DUTY SERIES FREE-STANDING HOT CUPBOARD - STATIC - W 900 MM - 2.0 KW

MODEL: PLH90

WEIGHTS & DIMENSIONS

Width	900 mil
Depth	600 mm
Height	900 mm
Weight	65.1 kg

SHIPPING DETAILS

Ship Width	100 cm
Ship Depth	81 cm
Ship Height	110 cm
Ship Weight	71.61 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	8.7 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	2000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	2 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Cabinet Size	Undercounter Height	Internal Width	855 mm
Construction Materials	Stainless Steel	Number of Shelf Positions	3
Control Type	Mechanical, On/Off	Number of Shelves	3
Heating System	Electric	Shelf Depth	530 mm
Humidity Generation	No	Shelf Width	850 mm
Insulated	Yes	Style	Enclosed Cabinet
Internal Depth	530 mm	Temperature Maximum	90 °C
Internal Height	700 mm	Temperature Minimum	30 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 25, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

