



**SILVERLINK 600**

#### PRODUCT OPTIONS AND ACCESSORIES

- SLS6V Lincat Silverlink 600 Free-standing Floor Stand - for V6 Series Ovens - W 600 mm
- V6/T V6 TOP COVER - ACCESSORY ONLY

#### PRODUCT FEATURES

- Fan assisted oven for superior heat distribution and reduced cooking times
- Excellent performance and optimum efficiency operating from a 13A plug
- Accommodates 2/3 gastronorms
- Rapid cool down feature
- Four shelf positions with two removable shelves
- Able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops
- Stainless steel interior with radiused corners and removable side shelf supports for easy cleaning

Cook with confidence with the Silverlink 600 Electric Oven, which comes with a fan assisted oven for superior heat distribution and reduced cooking times. Ideal for care homes as well as smaller pubs and restaurants, the oven, which accommodates 2/3 GN dishes and boasts a rapid cool down feature, guarantees excellent performance and optimum efficiency operating from a 13A plug. Multi-use, there are four shelf positions with two removable shelves, while the oven is also able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops.

AIA FILE NUMBER:

ITEM NUMBER:

#### WEIGHTS & DIMENSIONS

|        |         |
|--------|---------|
| Width  | 600 mil |
| Depth  | 623 mil |
| Height | 674 mil |
| Weight | 45.1 kg |

#### SHIPPING DETAILS

|                          |                                |
|--------------------------|--------------------------------|
| Ship Width               | 70.3 cm                        |
| Ship Depth               | 70.3 cm                        |
| Ship Height              | 102.3 cm                       |
| Ship Weight              | 49.61 kg                       |
| Ship Method              | Small Parcel (FedEx, UPS, DHL) |
| Shipping Package Type    | Pieces                         |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM        |
| Quick Ship Product       | No                             |

#### PRODUCT CERTIFICATIONS



#### ENERGY SPECS

|                           |          |                                      |               |
|---------------------------|----------|--------------------------------------|---------------|
| Primary Energy Type       | Electric | Electrical Plug Type                 | UK 3-Pin Plug |
| Electrical Total Amperage | 13 A     | Number of Electrical Plugs           | 1             |
| Electrical Volts          | 240V     | Electrical Connection Type           | Cord and Plug |
| Electrical Total Wattage  | 3000 W   | Number of Electrical Conductor Wires | 1             |
| Electrical Kilowatts      | 3 kW     | Dedicated Circuit Required           | No            |
| Electrical Phase          | 1-Phase  | Electrical Remarks                   | Single        |

#### ADDITIONAL SPECIFICATIONS

|                        |                                 |                             |           |
|------------------------|---------------------------------|-----------------------------|-----------|
| Construction Materials | Stainless Steel                 | Door Type                   | Solid     |
| Control Type           | Mechanical, Rotary Control Knob | Fan Assisted                | Yes       |
| Cooking Chamber Depth  | 335 mm                          | Gastronorm Capacity         | 1 x GN2/3 |
| Cooking Chamber Height | 420 mm                          | Number of Wire Racks        | 3         |
| Cooking Chamber Width  | 470 mm                          | Ventless Cooking Technology | No        |
| Cooking Rack Depth     | 335 mm                          | Temperature Maximum         | 250 °C    |
| Cooking Rack Width     | 455 mm                          | Temperature Minimum         | 50 °C     |

#### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

#### TECHNICAL DRAWING

