



## 36" SECTIONAL RANGE PLANCHA GRIDDLE

*Platinum Series*

**\*\* PLANCHA UNITS DO NOT ALLOW  
SPECIFIC TEMPERATURE OPERATION \*\***



Model Shown P36N-PPP

- P36N-PPP (Modular Mount with Plancha Griddle)
- P36C-PPP (Cabinet Base with Plancha Griddle)
- P36D-PPP (Standard-Oven Base with Plancha Griddle)
- P36A-PPP (Convection-Oven Base with Plancha Griddle)

Plancha units have a raised griddle plate for easy cleaning of cooking surface between loads. 3" wide collection on sides allow separation of waste for preparation of next fare. Plancha griddle is 1/2" thick reinforced steel plate powered by cast iron burners provides fast preheat and recovery time. High heat zone with max temperatures of 800°F located on front 2/3 of plate for quick sear with decreased temps on rear 1/3 of plate for product finishing.

### Standard Features

- 36" wide sectional range with 29-3/4" width plancha griddle available with a standard-oven base, convection-oven base, cabinet base or as a modular unit (for mounting on countertop, refrigerated or freezer base)
- Three 16,000 BTU NAT (15,500 BTU LP) cast iron burners with three manual control knobs
- Battery spark ignition
- 1/2" thick reinforced griddle plate
- Side and rear splashers
- 5" deep front rail
- Increased capacity removable stainless steel grease drawer
- Stainless steel front, sides, rear and exterior bottom
- Fully insulated lining and burner box
- 1-1/4" front gas manifold and 1" rear gas connection
- 5" high stainless steel flue riser
- Free battery-design assistance
- (1) year limited parts and labor warranty  
(reference <http://www.southbendnc.com/service.html> for limited warranty details)

### Standard Features of Oven-Base Models

- 45,000 BTU NAT (45,000 BTU LP) oven with standing pilot
- Heavy duty, stainless steel door handle
- Porcelain enamel interior
- Oven racks (2 for standard oven, 3 for convection oven)
- "Insta-On" thermostat ranging from 175°F to 550°F
- Standard-oven interior is large enough (26" by 26-1/2") for sheet pans to fit either way
- Convection-oven models have 1/2 hp, two-speed blower

### Standard Features of Cabinet-Base Models

- Stainless steel cabinet with removable doors that open from the center

### OPTIONS & ACCESSORIES AT ADDITIONAL COST

- |  |  |  |
|--|--|--|
| <input type="checkbox"/> External pressure regulator                           | <input type="checkbox"/> Casters (front two casters lock)  | <input type="checkbox"/> Open-frame base with casters for battery                  |
| <input type="checkbox"/> Front rail options:                                   | <input type="checkbox"/> Cable restraint kit (to restrict movement when on casters)                            | <input type="checkbox"/> Extra-deep rear-extending flue riser                      |
| <input type="checkbox"/> Cutouts in front rail for sauce pans                  | <input type="checkbox"/> 24" or 36" high flue riser  | <input type="checkbox"/> Stainless steel oven interior                             |
| <input type="checkbox"/> 7-1/4" deep front rail (to match old style sectional) | <input type="checkbox"/> Shelves on flue riser (one on 24" flue riser, one or two on 36" flue riser, 10" deep) | <input type="checkbox"/> Salamander or cheesemelter mounted on 36" high flue riser |
| <input type="checkbox"/> Square belly bar mounted on 7-1/4" deep front rail    | <input type="checkbox"/> Tray or tubular shelving (12" deep)   | <input type="checkbox"/> Removable shelf inside cabinet                            |
|  |  | <input type="checkbox"/> Electronic oven pilot ignition (no charge)                |

### STANDARD CONSTRUCTION SPECIFICATIONS

**Exterior Finish:** Front, sides, rear and exterior bottom constructed of #3 polished 430 and 304 stainless steel.

**Range:** 36"-wide front-manifold sectional range with 29-3/4" width 48,000 BTU NAT (46,500 BTU LP) plancha griddle with side and rear splashers and grease drawer.

**Front Rail:** 5" deep front rail.

**Flue Riser:** 5" high stainless steel flue riser

**Battery:** Unit can be in any position in a battery.

**Legs:** 6" stainless steel adjustable legs standard.

**Model 36D:** 45,000 BTU NAT (45,000 BTU LP) oven with standing pilot and thermostat range of 175°F to 550°F (79°C to 288°C). Porcelain enamel interior, measuring 14" high x 26" wide x 26.5" deep. Two racks with five-position side rails.


**Model 36A:** 45,000 BTU NAT (45,000 BTU LP) convection oven with standing pilot and thermostat range of 175°F to 550°F (79°C to 288°C). Porcelain enamel interior, measuring 14" high x 26" wide x 24" deep. Three racks with five-position side rails. Two-speed, 1/2 hp blower motor.

**Model 36C:** Stainless steel cabinet base with two removable doors that open from the center.



Approval Notes: \_\_\_\_\_

\_\_\_\_\_



**UTILITY INFORMATION**

**GAS:** Each unit has a 1-1/4" front manifold that couples to the adjacent sectional unit(s), and a 1" rear gas connection with a male NPT connector. Minimum gas supply pressure is 7" W.C. for natural gas and 11" W.C. for propane. All sectional units require a regulated gas supply (a pressure regulator must be ordered separately). If using a flexible-hose gas connection, the inside diameter of the hose must not be smaller than the connector on the unit and must comply with ANSI Z21.69, providing an adequate means of restraint to prevent undue strain on the gas connection.

**ELECTRICITY:** All oven models with optional electronic ignition require 50Hz or 60Hz single-phase power. 120V models have a 7-foot power cord with ground plug (5.9A for "A" models). 208/240V models have a terminal block for connection to a single-phase 208/240V source (2.7A for "A" models).

MODEL	GAS (BTU/HOUR)		ELECTRICITY (AMPS)	
	NATURAL	PROPANE	120V	208/240V
P36N-PPP	48,000	46,500	-	-
P36C-PPP	48,000	46,500	-	-
P36D-PPP	93,000	91,500	0*	0*
P36A-PPP	93,000	91,500	5.9*	2.7*

\*Standing Oven Pilot Models

**DIMENSIONS**

MODEL	SHIPPING CRATE DIMENSIONS & WEIGHT				
	WIDTH	HEIGHT	DEPTH	VOLUME	WEIGHT
P36N-PPP	45.5" (1156)	23" (584)	55" (1397)	33.3 cu ft (0.94 cu m)	375 lbs (170.1 kg)
P36C-PPP	45.5" (1156)	45" (1143)	55" (1397)	65.2 cu ft (1.85 cu m)	495 lbs (224.5 kg)
P36D-PPP	45.5" (1156)	45" (1143)	55" (1397)	65.2 cu ft (1.85 cu m)	601 lbs (272.6 kg)
P36A-PPP	45.5" (1156)	45" (1143)	55" (1397)	65.2 cu ft (1.85 cu m)	654 lbs (296.6 kg)

**MISCELLANEOUS**

- If casters are used with a flexible-hose gas connection, a restraining device should be used to prevent undue strain on the hose.
- Minimum clearance from noncombustible construction is zero (except there must be 2" clearance behind the blower motor of convection-oven models). Minimum clearance from combustible construction is 10" (254 mm) on sides and 12" (305 mm) on rear.
- Installation under a vented hood is recommended.

- Check local codes for fire and sanitary regulations.

**NOTICE:**

Southbend has a policy of continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

**DISCLAIMER**

1. **Oversized Cookware Use Policy** – "Oversized cookware is considered anything 12" in diameter or larger. Larger vessels may be used to straddle over open top grates (although efficiency may be lost when doing so). It is highly recommended when using oversized cookware that its use be limited to the rear portion of the range. IF oversized cookware is used on the front portion and hangs over onto the front rail, excessive heat may be driven and trapped in the front rail and can cause premature damage to the components housed there. This is easily avoided by never allowing cookware to overlap the front rail of the range. Electrical and other components housed in this area should see years of performance under normal intended use."

**INTENDED FOR COMMERCIAL USE ONLY.  
NOT FOR HOUSEHOLD USE.**

