



FIGURES IN BRACKETS INDICATE MILLIMETERS / DECIMAL AND FRACTIONAL DIMENSIONS EQUAL TO 1/32 INCH OR MINUS 1/16 INCH (1.5mm).

Weights	lb.	kg
Net	1225	555.7
Crated	1373	622.8

*For reference only

	cu. ft.	cu. m
Volume	84.8	2.40

Dimensions	in.	mm
Width	34-1/8	867
Depth	48-7/8	1242
Height	61-13/16	1570
Clearance	8 to 9-1/2 Adj.	203 to 241 Adj.

Mounted on standard legs

Electrical	Maximum Fuse Size			Minimum Ampacity			Poles (P) Wires (W)
	Left	Center	Right	Left	Center	Right	
208-230/60/3 water	25	20	20	19	16	16	3P 4W
200/50/60/3 water	25	20	20	19	16	16	3P 4W

This unit may be manufactured with other electrical characteristics and may have additional regulatory agency approvals. Consult the local Taylor distributor for other electrical characteristics and agency approvals based on specific electrical and country requirements.

(For exact electrical information, approval marks, and refrigerant, always refer to the data label of the unit.)

Continuing research results in steady improvements. Therefore, these specifications are subject to change without notice.

Bidding Specs

Electrical: Volt _____ Hz _____ ph _____
 Neutral: Yes No Cooling: Air Water NA

Options:

All options may not be available in combination with others or with all electrical or cooling configurations. Please consult your local Taylor distributor.

Authorized Taylor Distributor

Specifications

Electrical

Three dedicated electrical connections are required. See the electrical chart for the proper electrical requirements. Dispensing electrical connections must be permanently connected. Consult your local Taylor distributor for correct receptacle specifications as local codes allow.

Beater Motor

2.0 hp.

Water-Cooled Refrigeration System

Three / 1 in. FPT Connections / 10,000 BTU/hr. / R449A (BTUs may vary depending on compressor used.)

Separate Hopper Air-Cooled Refrigeration

One, 1,000 BTU/hr. R134A (BTUs may vary depending on compressor used.)

Clearance

Minimum Clearance of 3 in. (76 mm) on both sides and rear. Drip pan can be installed on either side. Allow 36 in. (914 mm) on the side drip pan is installed. Allow 36 in. (914 mm) in the rear for service access.

Options

- Dipping Cabinet (Consult your local Taylor distributor)
- Dipping Well (Consult your local Taylor distributor)
- Faucet



750 N. Blackhawk Blvd.
 Rockton, Illinois 61072
www.taylor-company.com