

Roll-In Freezers

- Improve the flow and function of your space by having frozen items where you need them most
- Solid door models
- Push carts directly into unit
- LED lighting



UCF633-SS31A



UCF666-SS71A

Model	Description	Voltage/Hz/Amps	Shipping Weight
UCF633-SS31A	Roll-in Freezer with Single Solid Door	115v / 60hz / 9.6	452 lb
UCF666-SS71A	Roll-in Freezer with Double Solid Door	115v / 60hz / 19.2	639 lb

Specifications

UCF633-SS31A dimensions: 89 3/4" H x 33 7/8" W x 46 1/2" D

UCF666-SS71A dimensions: 89 3/4" H x 66 7/8" W x 46 1/2" D

UCF633-SS31A: Environmentally friendly R290 refrigerant - 4.2 oz

UCF666-SS71A: Environmentally friendly R290 refrigerant - 8.2 oz

UCF633-SS31A: Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-15P

UCF666-SS71A: Factory pre-wired for dedicated outlet, 11 ft cord and plug included NEMA 5-20P

UCF633-SS31A volume: 35.8 cu ft

UCF666-SS71A volume: 79 cu ft

AISI 304 stainless steel interior and exterior with lock

Autodefroster

CFC-free high density polyurethane insulated cabinet

Electronic digital temperature control with alarms

Epoxy coated, sealed evaporator eliminates potential of corrosion

Fixed stainless steel loading ramp

High efficiency compressor, top mount

High efficiency evaporator coil & condenser


NSF/ANSI Standard 7 compliant

Temperature range: -13°F to 14°F




Product Specifications • Roll-In Freezers


Front UCFZ633 (Open)




Front UCFZ666 (Open)




Side UCFZ633/666






Top UCFZ633



Top UCFZ666



Back UCFZ633/666



Commercial Warranty

3 Year (parts & labor) / 5 year
sealed system (parts)

See complete warranty for details

