



The Auto-Saucer (RTU) is a high-performance rotary sauce dispensing system designed for shelf-stable, ready-to-mix pizza sauces. Built for speed and reliability, it applies sauce quickly, evenly, and with precise portion control directly onto the dough. The 22qt (5.5 gal) sauce vat supports high-volume production. Programming is fully customizable for up to 5 dough types and 5 sizes (6"-18"), with an optional cup fill feature. Each unit is factory-assembled, wet-tested, and ships ready to use. With plug-and-play setup, minimal training, low maintenance, and easy daily cleaning, the Auto-Saucer is the smart solution for consistent, efficient pizza prep.

AIA FILE NUMBER:

### PRODUCT OPTIONS AND ACCESSORIES

- Optional Accessories:
- 0111-302: Turntable Assembly 14" single
- 0111-303: Turntable Assembly 18" single
- 0111-532: Turntable Assembly Multi-Pan Step 6", 9", 11", 12", 13", 14"
- 0111-553: Turntable Assembly Multi-Pan Step 8", 10", 12", 14", 16"

#### Included Accessories:

- One Turntable
- Sauce Vat and Lid
- Dispensing and Priming Nozzles
- Dip Tube Assembly
- Strainer Assembly
- Cleaning Nozzle Adapter with Hose

### PRODUCT FEATURES

- Consistent saucing for each pizza
- Extremely high reliability
- Easy to train on and use
- Low maintenance
- Plug 'n Play
- Customizable for up to 5 dough types
- 5 Programmable pizza sizes ranging from 6" - 18"
- Portion control and minimized waste
- ~22qt / 5.5gal sauce vat
- Built-In NSF approved cleaning program utilizing Stera-Sheen Green Label chemical to make the cleaning and sanitizing process simple

ITEM NUMBER:

# MODEL: RSD-1-RTU-XCWSS-XXXX

### WEIGHTS & DIMENSIONS

Width	22.25 in
Depth	28.375 in
Height	44.375 in
Weight	90 lb
Dimensions (WxDxH)	22.25 Inch X 28.375 Inch X 44.375 Inch
Clearance Required: Top	2 in
Clearance Required: Front	4 in
Clearance Required: Back	6 in
Clearance Required: Left Side	1.25 in
Clearance Required: Right Side	1.25 in

### WATER, PLUMBING, AND DRAINAGE SPECIFICATIONS

Water Line Required	No
Drain Line Required	No

### ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	110V
Electrical Total Amperage	2.5 A
Electrical Amps Per Conductor	2.5
Electrical Total Wattage	275 W
Electrical Kilowatts	0.275 kW
Electrical Phase	1PH
Electrical Hertz	60 Hz
Electrical Connection Type	Cord and Plug

### ADDITIONAL SPECIFICATIONS

Capacity: Sauce	5.5 gal
Construction Materials	Stainless Steel
Construction Remarks	Stainless Steel Top, Roto-Molded Polyethylene Enclosure and Base
Number of Dough Types	5
Number of Pizza Sizes	5

### SHIPPING DETAILS

Ship Width	40 in
Ship Depth	48 in
Ship Height	53 in
Ship Weight	150 lb
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	95688
Freight Class (NMFC)	92.5
Quick Ship Product (Official Commercial Foodservice Program)	No
Ship Lead Time	40

### PRODUCT CERTIFICATIONS



Electrical Plug Type	Three Prong Grounding Plug (NEMA 5-15P)
Number of Electrical Plugs	1
Number of Electrical Conductor Wires	3
Dedicated Circuit Required	No
Electrical Remarks	Grounded outlet required within 3' of the Auto-Saucer. Compatible with 50/60Hz - 110VAC, 2.5A / 240VAC 1.5A

# MODEL: RSD-1-RTU-XCWSS-XXXX

### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

### TECHNICAL DRAWING

